

| TECAPRO®



FIT FOR ANY PURPOSE

TECAPRO®
BD 9311 – 335 g/m²

HEAT & FLAME PERFORMANCE WITH ANTI-STATIC

Protects against industrial heat and flame hazards.










NATURAL COTTON COMFORT




Feels soft while providing good moisture management properties.

HIGH DURABILITY

Developed to withstand repeated usage as well as domestic and industrial laundering.

TECHNICAL DATA	TECAPRO®	TEST METHOD
Quality	BD 9311	
Width	152 cm (+2/-1 cm)	ISO 22198: 2006
Weight	335 g/m² (± 5%)	ISO 3801: 1977
Composition	cotton/Static-Control™ 99/1%	ISO 3572: 1976
Construction	3/1 S twill	ISO 1833: 2020
Available finishes	Durable flame-retardant finish with Comfort-Control	

Physical performance		
Tensile strength	1300 N x 600 N (±10%)	ISO 13934-1: 2013
Care labelling		
Domestic laundering	    	
Industrial laundering	75 °C	
Protection	Multi-risk protection	
PPE requirements*	   	

CERTIFICATION*		
	Industrial flame & heat hazards	EN ISO 11612 A1,A2,B1,C1,E2,F1: 2015 (A1 + A2= 50 x ISO 15797 - 75 °C)**
	Electric Arc	EN IEC 61482-1-2, class 1: 2015
	Welding	EN ISO 11611, class 1: 2015
	Anti-Static for explosion risk	EN 1149-5: 2018, testmethod EN 1149-3: 2004
	General requirements***	EN ISO 13688: 2013

* Copyright symbols: NEN, Delft (Netherlands).

** After pre-treatment (according to ISO 15797, 1 wash procedure 8 (75 °C) and 1 tumble drying (procedure A) (max. 70 °C outlet temperature).

*** Tested on specific colours.

COLOURS

Black 42134	Sapphire 40458	Caledo 47240	Durango 40803
----------------	-------------------	-----------------	------------------

The colours shown are standard options available with a minimum order of 100 meters. This service program is subject to change. Please scan the QR code or visit [our website](#) for the latest overview of standard colours.



For any additional colours or specific colour combination requirements beyond this service, please contact your TenCate Protective Fabrics representative.

Ten Cate Protect B.V. is certified according:



Product certification:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.