

**TECASAFE®**  
Ecogreen®



## PROVEN COMFORT IN ANY SITUATION



**TECASAFE® ECOGREEN®**  
**XL 9240 – 240 g/m<sup>2</sup>**

### GUARANTEED COMFORT IN ANY SITUATION

Soft, silky natural fibres provide superior moisture management, keeping you comfortable, cool and dry at all times thanks to advanced breathability.

### LASTING LOOKS EVEN WITH FREQUENT WASHING

High durability maximises the lifetime of your protective workwear, with an excellent colour fastness rating of 4-5 after 50 industrial washing cycles (ISO 15797).

### FIRST ECO-FRIENDLY INHERENT FR FABRIC WITH CLOSE TO 50% SUSTAINABLE MATERIALS

Lowers your footprint without compromising on the best inherent FR multi-norm performance. Featuring sustainably-sourced eco-friendly TENCEL™ Lyocell, with EPD® for measurable impact.



TECHNICAL DATA	TECASAFE® ECOGREEN®	TEST METHOD
Quality	XL 9240	
Width	152 cm (+2/-1 cm)	ISO 22198: 2006
Weight	240 g/m <sup>2</sup> (± 5%)	ISO 3801: 1977
Composition	Modacrylic/TENCEL™ Lyocell/ para-aramid/Static-Control™	ISO 3572: 1976
Construction	2/1 twill	ISO 1833: 2020
Available finishes	Standard: Hydro-Tec. Optional: Comfort	
<b>Physical performance</b>		
Tensile strength	900 N x 650 N (±10%)**	ISO 13934-1: 2013
<b>Care labelling</b>		
Domestic laundering		
Industrial laundering	75 °C Colour: White:	
PPE requirements*		

\* Copyright symbols: NEN, Delft (Netherlands) \*\* Hydro-Tec finish only

CERTIFICATION		
	Industrial flame & heat hazards	EN ISO 11612 A1,A2,B1,C1,E2,F1: 2015 (A1 + A2= 100 x ISO 15797 - 75 °C)
	Wildland fire fighting	EN 15614: 2007
	Welding	EN ISO 11611, class 1: 2015***
	Electric Arc	EN IEC 61482-1-1: 2019 HRC/Category 2 (8 ≤ ATPV ≤ 25 cal/cm <sup>2</sup> )
	Anti-Static for explosion risk	EN 1149-5: 2018, EN 1149-3: 2004
	Liquid chemicals**	EN 13034: 2005 + A1: 2009
	High Visibility colour: Yellow Contrast colours are available	EN ISO 20471: 2013
	General requirements****	EN ISO 13688: 2013
	OEKO-TEX® STANDARD 100, class 2	Centexbel, no. 0903009

\*\* Hydro-Tec finish only \*\*\* Although this fabric full-fills the requirements of EN ISO 11611, fabrics out of the Tecasafe® Ecogreen collection are more suitable for welding applications \*\*\*\* Tested on specific colours

COLOURS			
Intense blue 89350	Black velvet 89254	Moonmist 89253	Delftblue 89249
Ribbon red 89252	Sunrise orange 89305	Yellow (EN 20471) 89251	

The colours shown are standard options available with a minimum order of 100 meters. This service program is subject to change. Please scan the QR code or visit [our website](#) for the latest overview of standard colours.

For any additional colours or specific colour combination requirements beyond this service, please contact your TenCate Protective Fabrics representative.

Ten Cate Protect B.V. is certified according:



Member of ETSA



This fabric comes with an EPD® (Environmental Product Declaration); an independently verified and registered document that communicates information about the life-cycle environmental impact of products.

All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.