

TECAWORK®



**ANY WORK,
ANYWHERE**

TECAWORK® RIPSTOP
KG 246 – 245 g/m²

TOUGH AND ROBUST

For workwear that combines comfort and ultimate performance.

HEAVY-DUTY FABRIC

Heavy-duty and reinforced grid weave makes the fabric resistant to tearing.

COMFORTABLE

Tecawork® Ripstop has a fine and smooth structure enhancing wearer comfort.

TECHNICAL DATA	TECAWORK® RIPSTOP	TEST METHOD
Quality	KG 246	
Width	153 cm (+2/-1 cm)	ISO 22198: 2006
Weight	245 g/m ² (± 5%)	ISO 3801: 1978
Composition	Polyester/cotton 65/35%	ISO 1833: 2020
Construction	Ripstop	ISO 3572: 1976
Available finishes	Easy-Care	

Physical performance		
Tensile strength	1200 N x 1000 N (±10%)	ISO 13934-1: 2013
Dimensional change	<3%	ISO 5077: 2007 After 5x cleaning cycles at 75 °C ISO 15797: 2018

Care labelling		
Domestic laundering		NEN-EN-ISO 6330, 6N 60 °C: 2013
Industrial laundering	75 °C - ISO 15797 White: Colour:	Visit our website for the laundrying recommendations www.tencatefabrics.com Qualification label - ISO 30023

CERTIFICATION		
	Öko-Tex Standard 100, class 2	Shirley, no. 11-43863

COLOURS					
Papaya 65293	Royal box 60624	Mood indigo 66213	Everglade 65522	Charcoal 60380	Black 60475

Ten Cate Protect B.V.
is certified according:



Member of:



All mentioned data must be considered as indicative values. To the best of our knowledge all information contained herein is accurate. TenCate Protective Fabrics Europe declines any form of liability related to the use of the attached specimen that shall be regarded as a sample only and therefore not meant to be used in any form of garment making.